



FLEXIBLE AIR DUCT HOSE

Product Type:

Air and Defroster Systems

Recommended for:

Connections between hot air sources with air cleaners or other aggregates. After being formed; it retains its original shape.

Resistant to:

Resistant to the harmful conditions under the bonnet; heat, ozone and coolant additives


Construction:

Shape: Straight
Tube: Aluminium
Reinforcement: -
Wire: -
Cover: -

Standards:

SAE Norm -
Din Norm -

Temperature:



Gates	PN	↔		∅	▬	▬	⌚
		mm	"	mm	m	m	bar
FD19005	7743-00519	19	3/4	20	0.5	0.2	0.2
FD19010	7743-01019	19	3/4	20	1	0.4	0.2
FD22005	7743-00522	22	7/8	23	0.5	0.2	0.2
FD22010	7743-01022	22	7/8	23	1	0.4	0.2
FD25005	7743-00525	25	1	26	0.5	0.2	0.2
FD25010	7743-01025	25	1	26	1	0.4	0.2
FD35010	7743-01035	35	1 3/8	36	1	0.4	0.2
FD38005	7743-00538	38	1 1/2	39	0.5	0.2	0.2
FD38010	7743-01038	38	1 1/2	39	1	0.4	0.2
FD40005	7743-00540	40	1 9/16	41	0.5	0.2	0.2
FD40010	7743-01040	40	1 9/16	41	1	0.4	0.2
FD45005	7743-00545	45	1 3/4	46	0.5	0.2	0.2
FD45010	7743-01045	45	1 3/4	46	1	0.4	0.2
FD50005	7743-00550	50	2	51	0.5	0.2	0.2
FD50010	7743-01050	50	2	51	1	0.4	0.2
FD52010	7743-01052	52	2	53	1	0.4	0.2
FD52013	7743-01352	52	2	53	1.3	0.545	0.2
FD55005	7743-00555	55	2 1/5	56	0.5	0.2	0.2
FD55010	7743-01055	55	2 1/5	56	1	0.4	0.2
FD60005	7743-00560	60	2 3/8	61	0.5	0.2	0.2
FD60010	7743-01060	60	2 3/8	61	1	0.4	0.2