

Product Type:

Fuel Systems

Recommended for:

Clamped hose applications on all fuel systems, including fuel injection systems. Specially designed for fuel circuits (leaded and unleaded petrol, diesel) in passenger cars. Approved for transportation of E-10, E-15, E-85.

Resistant to:

Tube resists heat and oil. Cover resists heat, oil, ozone and weathering.

Construction:

Shape: Straight
Tube: Nitrile (NBR)
Reinforcement: Synthetic
Wire: -
Cover: NBR/PVC

Standards:

SAE Norm SAE J30R7
Din Norm DIN 73379

Temperature:


	PN								
		mm	"	mm	m	mm	bar	bar	mm/HG
FL03215	3225-00050	3.2	7/64	8	15	71	7.5	30	608
FL04015	3225-00051	4	5/32	9	15	75	7.5	30	608
FL05015	3225-00055	5	13/64	10	15	76	7.5	30	608
FL06015	3225-00052	6	1/4	12	15	79	7.5	30	608
FL07015	3225-00056	7	9/32	13	15	89	7.5	30	608
FL08015	3225-00053	8	5/16	14	15	91	7.5	30	608
FL10010	3225-00054	10	3/8	16	10	114	7.5	30	608
FL10015	3225-10014	10	3/8	16	15	114	7.5	30	608
FL12015	3225-10015	12	15/32	19	15	127	7.5	30	608