



Optimale prestaties



Flexibele opslag



Betrouwbaarheid



Compact

EC-serie 3-7.5 kW - 11 bar

| Model | Artikelnummer | Compressor | | Tank | | Pomp | rpm | l/min | dB(A) | volt | LxBxH in mm | KG |
|----------------|---------------|------------|-----|------|-----|-------|------|-------|-------|----------|---------------|-----|
| | | PK | kW | bar | L | | | | | | | |
| EC 553/270 | 4116025814 | 4 | 3 | 11 | 270 | NS31 | 1300 | 300 | 73 | 400/3/50 | 1670x555x1040 | 135 |
| EC 653/270 YD | 6250367830 | 5.5 | 4 | 11 | 270 | NS39 | 1000 | 450 | 75 | 400/3/50 | 1670x555x1040 | 155 |
| EC 827/500 YD | 6270336730 | 7.5 | 5.5 | 11 | 500 | NS39 | 1250 | 570 | 82 | 400/3/50 | 1940x600x1315 | 220 |
| EC 950/500 YD | 6250369330 | 7.5 | 5.5 | 11 | 500 | NS59S | 750 | 620 | 82 | 400/3/50 | 1940x600x1315 | 245 |
| EC 1210/500 YD | 6250369930 | 10 | 7.5 | 11 | 500 | NS59S | 900 | 900 | 82 | 400/3/50 | 1940x600x1315 | 270 |

EC-serie 3-7.5 kW - 15 bar

| Model | Artikelnummer | Compressor | | Tank | | Pomp | rpm | l/min | dB(A) | volt | LxBxH in mm | KG |
|-----------------|---------------|------------|-----|------|------|-------|------|-------|-------|----------|---------------|-----|
| | | PK | kW | bar | L | | | | | | | |
| EC 418/270 | 4116025987 | 4 | 3 | 15 | 270 | NS31 | 984 | 275 | 73 | 400/3/50 | 1670x555x1040 | 160 |
| EC 522/270 YD | 4116023266 | 5.5 | 4 | 15 | 300 | NS39 | 800 | 395 | 75 | 400/3/50 | 1670x555x1040 | 180 |
| EC 522/270V YD* | 4116023265 | 5.5 | 4 | 15 | 270V | NS39 | 800 | 395 | 75 | 400/3/50 | 835x600x1950 | 170 |
| EC 626/500 YD | 4116023269 | 7.5 | 5.5 | 15 | 500 | NS39 | 1000 | 470 | 82 | 400/3/50 | 1940x600x1315 | 250 |
| EC 760/500 YD | 4116023267 | 7.5 | 5.5 | 15 | 500 | NS59S | 600 | 570 | 82 | 400/3/50 | 1940x600x1315 | 275 |
| EC 942/500 YD | 4116023268 | 10 | 7.5 | 15 | 500 | NS59S | 750 | 705 | 82 | 400/3/50 | 1940x600x1315 | 280 |

*Uitgevoerd met een verticale persluchtketel, ideaal voor kleinere ruimtes.

YD = ster-driehoekstart