


Betrouwbaar

**Laag
geluidsniveau**

**Gebruik-
svriendelijk**

**Continu
gebruik**

RCA Mini 2.2-5.5 kW

Model	Artikelnummer	PK		bar	L *	droger	l/min	dB(A)	volt	LxBxH in mm	KG
		PK	kW								
RCA 2.2 (230V)	4152050867	3	2.2	10	0	nee	294	61	230/1/50	620x630x950	110
	4152050869				200	nee				1430x600x1260	165
	4152050873				200	ja				1430x600x1260	190
RCA 2.2 (400V)	4152050807	3	2.2	10	0	nee	294	61	400/3/50	620x630x950	110
	4152050809				200	nee				1430x600x1260	165
	4152050813				200	ja				1430x600x1260	190
RCA 3	4152050817	4	3	10	0	nee	366	61	400/3/50	620x630x950	115
	4152050819				200	nee				1430x600x1260	170
	4152050823				200	ja				1430x600x1260	195
RCA 4	4152050837	5.5	4	10	0	nee	516	62	400/3/50	620x630x950	120
	4152050839				200	nee				1430x600x1260	175
	4152050843				200	ja				1430x600x1260	200
RCA 5.5	4152050847	7.5	5.5	10	0	nee	780	66	400/3/50	620x630x950	130
	4152050849				200	nee				1430x600x1260	185
	4152050853				200	ja				1430x600x1260	210

* Optioneel af-fabriek verkrijgbaar op ketel met inhoud van 270 of 500 liter.

Prestaties van de eenheid gemeten volgens ISO 1217, Bijlage C, laatste editie. Geluidsniveau gemeten volgens ISO 2151:2004