

Modlight70 Pro buzzer

4 tones

Buzzer modules

[Link naar het product](#)

Afbeelding



Product van afwijken van afbeelding



Classifications

ECLASS-6.0	27371200
ECLASS-6.1	27371237
ECLASS-7.0	27371237
ECLASS-8.0	27371237
ECLASS-9.0	27371237
ECLASS-10.1	27371237
ECLASS-11.1	27371237
ECLASS-12.0	27371237
ETIM-5.0	EC001152

Electrical data | Supply

Operating voltage DC	24 V
Operating voltage DC min.	21,6 V
Operating voltage DC max.	26,4 V
Current consumption max.	62,5 mA

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Protection degree additional condition	inserted, locked

Mechanical data | Material data

Material housing	PC
------------------	----

Mechanical data | Mounting data

Height	49 mm
Width	70 mm

Depth	70 mm
-------	-------

Environmental characteristics | Climatic

Operating temperature min.	-30 °C
----------------------------	--------

Operating temperature max.	60 °C
----------------------------	-------

Connection type 1

Mounting method	bayonet-locking
-----------------	-----------------

Commerciële gegevens

Douane tarief nummer	85318070
----------------------	----------

GTIN	4048879752497
------	---------------

Verpakkingseenheid	1
--------------------	---