










Betrouwbaar

**Laag
geluidsniveau**

**Gebruik-
svriendelijk**

**Continu
gebruik**

RCA Mini 2.2-5.5 kW

Model	Artikelnummer																
		PK	kW	bar	L *	droger	l/min	dB(A)	volt	LxBxH in mm	KG						
RCA 2.2 (230V)	4152050867	3	2.2	10	0	nee	294	61	230/1/50	620x630x950	110						
	200				nee	1430x600x1260				165							
	200				ja	1430x600x1260				190							
RCA 2.2 (400V)	4152050807	3	2.2	10	0	nee	294	61	400/3/50	620x630x950	110						
	200				nee	1430x600x1260				165							
	200				ja	1430x600x1260				190							
RCA 3	4152050817	4	3	10	0	nee	366	61	400/3/50	620x630x950	115						
	200				nee	1430x600x1260				170							
	200				ja	1430x600x1260				195							
RCA 4	4152050837	5.5	4	10	0	nee	516	62	400/3/50	620x630x950	120						
	200				nee	1430x600x1260				175							
	200				ja	1430x600x1260				200							
RCA 5.5	4152050847	7.5	5.5	10	0	nee	780	66	400/3/50	620x630x950	130						
	200				nee	1430x600x1260				185							
	200				ja	1430x600x1260				210							

* Optioneel af-fabriek verkrijgbaar op ketel met inhoud van 270 of 500 liter.

Prestaties van de eenheid gemeten volgens ISO 1217, Bijlage C, laatste editie. Geluidsniveau gemeten volgens ISO 2151:2004