

Partner of specialist dealers!

The bully 1000 TST for perfect cleaning results!

- Space-saving, compact and service-friendly design
- Extremely stable and robust Roto-Mold trolley
- Integrated trolley takes steps and rough ground in its stride
- Simple and comfortable handling
- Corrosion-resistant materials
- Integrated hose drum with foldable crank (TST)
- 7.5 m power lead with cable reel
- Trigger gun with safety catch and quick release system
- Dirtkiller lance with stainless steel pipe and quick release nipple, stainless steel lance with flat jet nozzle and quick release nipple
- Storage for trigger gun with safety catch and lance
- Total-stop-system
- Shock absorbing buffers





Germany



| Technical specifications | bully 1000 TST |
|---|-----------------------|
| Ord. no. | 40.360 10 |
| Operating pressure, continuously adjustable | 30-200 bar (3-20 MPa) |
| Max. admissible overpressure | 230 bar (23 MPa) |
| Water output | 16 l/min (960 l/h) |
| Motor speed | 1,400 rpm |
| Connected load | 400 V, 12 A, 50 Hz |
| Power intake / Power output | 7.5 kW / 5.5 kW |
| Weight | 68 kg |

| Features & Equipment | Ord. no. |
|---|--------------|
| Steel braided high-pressure hose NW 8, 15 m | 46.411 |
| Trigger gun M2000 with safety catch and quick release system | 12.492 |
| Dirtkiller lance 1000 mm with stainless steel pipe and quick release nipple | 12.425-055 |
| Stainless steel lance 1000 mm with flat jet nozzle and quick release nipple | 12.420-D2505 |



kranzle

The WS 1000 TS offers stationary

power in a compact format!

- Carrying frame and cover of stainless steel
- Available as a standing unit and wall-mounted alike
- 7.5 m power lead
- Trigger gun with safety catch and quick release system
- Stainless steel lance with flat jet nozzle and quick release nipple
- Storage for trigger gun with safety catch and lance
- Total-stop-system with delayed motor cut-off
- Safety deactivation after 20 min without operation
- Stainless steel pressure gauge
- Steel braided high-pressure hose

Optional:

■ Turbokiller with stainless steel lance and quick release nipple





■ Made

Germany

| Technical specifications | WS 1000 TS |
|---|-----------------------|
| Ord. no. | 41.313 10 |
| Operating pressure, continuously adjustable | 30-200 bar / 3-22 MPa |
| Max. admissible overpressure | 230 bar / 23 Mpa |
| Water output | 16 l/min (960 l/h) |
| Motor speed | 1,400 rpm |
| Connected load | 400 V, 12 A, 50 Hz |
| Power intake / Power output | 7.5 kW / 5.5 kW |
| Weight | 62 kg |
| Features & Equipment | Ord. no. |
| Steel braided high-pressure hose NW 8, 10 m | 44.878 |
| Trigger gun Starlet with safety catch and quick | |

| reatures & Equipment | Ora. no. |
|---|--------------|
| Steel braided high-pressure hose NW 8, 10 m | 44.878 |
| Trigger gun Starlet with safety catch and quick release system | 12.327 2 |
| Stainless steel lance with flat jet nozzle and quick release nipple | 12.420-D2505 |
| Water intake filter | 13.310 |
| | |

| Optional | Ord. no. |
|--|------------|
| Turbokiller with stainless steel lance with plug-in nipple | 12.430-055 |